

• TRUSTED QUALITY SINCE 1921 •



CONCRETE AND MORTAR REPAIR

DESCRIPTION AND USES

Rust-Oleum® Concrete and Mortar Repair is a ready-to-use, waterproof sealant formulated to repair cracks and holes in concrete, mortar, and masonry surfaces. It contains silicone additives for outstanding adhesion, flexibility, and water resistance. It forms a durable, 100% waterproof and weatherproof seal. Resists gas, oil, grease, and salt. Paintable. Easy to apply, low odor and water clean-up. VOC compliant. Interior/exterior use.

PRODUCT FEATURES

- Fills and seals cracks and holes in concrete surfaces
- Ready to use – needs no mixing or additives
- Provides a durable, long-lasting repair that is resistant to gasoline, salt, grease, or oil when cured
- 100% waterproof & weatherproof seal
- Excellent flexibility & adhesion
- Paintable
- Easy water clean-up
- Exterior/interior use
- Low odor & VOC compliant

PRODUCT

SKU	DESCRIPTION
391310	10.1 Ounce Cartridge

PRODUCT APPLICATION

SURFACE PREPARATION

All surfaces must be clean, dry, structurally sound, and free of all foreign material. Joint size should not exceed 1/2" wide x 1/2" deep. If joint depth exceeds 1/2", use backer rod material. Not for continuous underwater use, filling butt joints, surface defects, tuck-pointing or expansion joints.

PRODUCT APPLICATION (cont.)

APPLICATION

Apply only when air, material, and surface temperatures are between 40-100°F (4-38°C). Do not apply when rain or freezing temperatures are forecasted within 24 hours. Cooler temperatures and higher humidity will slow down dry time.

Cut nozzle at 45° angle to desired bead size. Load cartridge into caulk gun. Fill cracks and gaps with sealant. After application, a more uniform fill or neater appearance may be obtained by tooling lightly with a trowel or putty knife.

COVERAGE

The 10.1-ounce size will cover up to 55 linear feet at 3/16" diameter bead. Actual coverage will vary depending upon application method.

DRY & RECOAT TIMES

- Tooling Time (Working Time) - 10 minutes
- Tack Free Time - 30 minutes
- Paintable after 2 hours with latex or oil-based paints.
- Return to Service Time - 24 hours
- Full Dry Through - 7-14 days
(longer in cool and/or humid conditions)

CLEAN-UP

Clean up excess wet sealant with a damp sponge before it skins over. Excess dried sealant will need to be cut or scraped away. Wash hands or skin with soap and water.

• TRUSTED QUALITY SINCE 1921 •



CONCRETE AND MORTAR REPAIR

PHYSICAL PROPERTIES

		CONCRETE AND MORTAR REPAIR
Resin Type		Acrylic Latex
Solvents		Water
Weight	Per Gallon	13.2 lbs.
Solids	By Weight	81%
VOC		9.5 g/l
Practical Coverage		Up to 55 linear feet at 3/16" diameter bead depending on application
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity*	Tooling Time	10 minutes
	Tack Free	30 minutes
	Traffic Time	24 hours
	Full Cure	7-14 days
Shelf Life		1 year
Flash Point		212°F (100°C)
Safety Information		For additional information, see SDS

*Longer in cool and/or humid conditions.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.